

FIRE SEALS

FIRE SEALS

LP1004, LP1504, LP2004, LP2504


Our intumescent fire door seals offer fire protection where no smoke sealing is required. Combine a fire seal with a Batwing® seal for acoustic + smoke containment. Available in a choice of sizes to cover 30 + 60 minute applications, the fire seal also includes integral antimicrobial protection.



ACOUSTIC, SMOKE + FIRE SEALS




LP1004 Fire seal




LP1504 Fire seal



LP2004 Fire seal



LP2504 Fire seal



Fire seal

SYSTEM SPECIFICATIONS

Test evidence

- ▶ Fire: BS EN 1634-1: 2008.
- ▶ Fire: BS 476-22: 1987.

Performance

- ▶ Protects against fire.
- ▶ Integral antimicrobial protection.

Size

- ▶ 10 x 4mm.
- ▶ 15 x 4mm.
- ▶ 20 x 4mm.
- ▶ 25 x 4mm.
- ▶ Other sizes available, please ask for details.

Location

- ▶ Single and double leaf doors.

Use with

- ▶ Smoke seals and any architectural seals.

Min/max gap size

- ▶ 3mm/4mm.

Seal material

- ▶ PVC encased sodium silicate.

Standard lengths

- ▶ 1m and 2.1m.
- ▶ Other lengths to special order.

Fixing

- ▶ Heavy duty self-adhesive backing tape.

Finishes

- ▶ Available in a range of standard colours, plus woodgrain and metallic finishes for superior aesthetics.

Accreditations

