


TREND

CE1220TND



ITEM SIZE (mm)

12 x 20

GROOVE SIZE (mm)

12,1 x 20

AVAILABLE LENGTHS (mm)

330 - 430 - 530 - 630 - 730 - 830 - 930 - 1030 - 1130 - 1230

MATERIALS

EXTERNAL PROFILE 6060 T6 aluminium alloy

INTERNAL PROFILE 6060 T6 aluminium alloy

AVAILABLE FINISHING Mill

MECHANISMS Nylon PA6 30% Fiberglass reinforced

SEAL CA. Tri-extruded tubular seal in self-extinguishing TPE

CLOSING END-CAP Included. Nylon PA6 30% Fiberglass reinforced. Color: black.

ACTIVATION PLUNGER 1. Self-directing articulated metal plunger with nylon cap, adjustable with a 3 mm Allen wrench.
Colour: black.

TECHNICAL CHARACTERISTICS

MAXIMUM DROP (mm) 14

WORKING TEMPERATURES (c°) -35° / + 200°

FIXING TYPE 3F. removing the inner profile (screws not included).

CERTIFICATES

WORKING CYCLES > 200.000 (internal test)

ACOUSTIC INSULATION /

FIRE RESISTANCE /

SMOKE TESTED /



APPROVED PRODUCT
CF 5995

* See certificate for universal matrix for the field of application

TREND

CE1220TND

ITEM LENGHT mm	ITEM WEIGHT Kgs	BOX WEIGHT Kgs	MAX TRIMMING mm	TRIMMING from -> to mm
330	0,104	6,94	50	330 -> 280
430	0,136	8,86	135	430 -> 295
530	0,168	10,78	200	530 -> 330
630	0,200	12,70	200	630 -> 430
730	0,232	14,62	200	730 -> 530
830	0,264	16,54	200	830 -> 630
930	0,296	18,46	200	930 -> 730
1030	0,328	20,38	200	1030 -> 830
1130	0,360	22,30	200	1130 -> 930
1230	0,392	24,22	200	1230 -> 1030
1330	/	/	/	/
1430	/	/	/	/
1530	/	/	/	/
1630	/	/	/	/
1730	/	/	/	/
1830	/	/	/	/

PACKAGING

MINIMUM PACKAGING 5 pieces

BOX PACKAGING 60 pieces (except where noted)

ITEM AND PACKAGING CARE

Keep the items inside their original packaging. Keep the boxes in horizontal position, do not bend or overlap heavy weights.

Keep stored in a dry place, protected from water, solvents and direct sunlight.