



GB - EN

			
1213		2538	
Tremco CPG Netherlands B.V Vlietskade 1032 NL-4241 Arkel			
14		22	
FS703-20230801 nullifire.com/FS703			
EN 15651-1, -2: 2012			
Non-structural sealant for joints for interior and exterior application (intended for use in cold climates)			
Non-structural sealant for sealing glazing applications (intended for use in cold climates)			
- Type F-EXT-INT-CC 25LM, Type G-CC 25LM - Conditioning: Method A - Substrate: Aluminium			
REACTION TO FIRE		Class E	
RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH		NPD	
WATER TIGHTNESS AND AIR TIGHTNESS			
- Resistance to flow		≤ 3mm	
- Loss of volume		≤ 10%	
- adhesion/cohesion properties at maintained extension after water immersion (23°C)		NF	
- elastic recovery		≥60 %	
- adhesion/cohesion properties after exposure to heat, water and artificial light		NF	
- adhesion/cohesion properties (-30°C)		≤ 0,9 N/mm ²	
- adhesion/cohesion properties at maintained extension (-30°C)		NF	
DURABILITY		Passed	

NF = no failure according to ISO 11600

NPD = No performance declared